- High compatibility and stability
- Type approval with CCS



- Designed to use for emergency purpose on life raft.
- Adopts low consumption design to ensure the product to continuously operate more than 96 hours.
- The Search and Rescue Radar Transponder (SART) is a 9 GHz receiver / transmitter which provides a position.
- The fundamental function of the SART is to indicate its position by producing range and bearing information on any 9 GHz radar screen of any nearby vessels and aircraft.
- When its RADAR receiver is triggered by an interrogating RADAR of 9 GHz band on a search and rescue ship or aircraft, the SART immediately transmits a coded response signal (a series of 12 dots).
- Conforms to the latest standards including IMO A.802 (19), IMO MSC.510 (105) and IEC 61097-1.







SPECIFICATIONS

• TECHNICAL SPECIFICATIONS

- TX Frequency: 9.2∼9.5 GHz
- Polarization: Horizontal
- Radiated Power: 400 mW E.I.R.P
- Receiver Sensitivity: Better than -50 dBm

• BATTERY REQUIREMENTS (NBT100)

- Battery Voltage: DC 9 V - Storage Temp: $-30^{\circ}\text{C} \sim +70^{\circ}\text{C}$

Storage Life: Max 5 years on board (plus one year of shelf time)
 Operating hours: ≥96 hours standby + 8 hours continuous transmission

(interrogated with a pulse repetition frequency 1Hz)

SIZE & WEIGHT

- Size: 95 (D) \times 377 (L) mm

- Weight: 750 g

WORKING ENVIRONMENTS

- Operating Temp: -20°C∼+55°C
- Floating Type: Floatable
- IP Grade: IP67

EQUIPMENT LIST

• STANDARD

- Transponder NRT-1000 1 pc
- Mounting Bracket 1 pc

- Tele-Pole (1.5 m) 1 pc

- Accessories 1 set



SIZE DIMENSION 42.15 61 75 TRANSPONDER MOUNTING BRACKET

