EX-PRO HANDHELD PHONE

NSR Fire-fighter's portable radiotelephone:

- Meet IMO MSC.338 (91) and IMO MSC.149 (77) regulation
- Designed for onboard fire-fighter's communication
- Ex-proof certificated
- Type approval with CCS



According to IMO MSC.338 (91) & SOLAS Chapter II-2, regulation 10.10.4:

Fire-fighter's communication

A minimum of TWO two-way portable radiotelephone apparatus for each fire party for fire-fighter's communication shall be carried on board. Those two-way portable radiotelephone apparatus shall be of an explosion-proof type or intrinsically safe.









SPECIFICATIONS

FREQUENCY & CHANNEL

- Frequency Range: 156.300~156.875 MHz

- Channel Space: 25 kHz

- Usable Channels: 19 channels (default)

• TECHNICAL FEATURE

- Communication Methods:

- Output Power: High 3.0 W / Low 0.5 W

Simplex - Warming Up Time: Within 5 sec - Squelch Control: - Dual Watch: - Key Locking: - Battery Save Mode: - Beep Establishment:

- Location Indication:

- Operating Temperature: -20°C~+60°C

- Size: 256 (H) \times 56 (W) \times 46.2 (D) mm - Weight: 280 g (Transceiver + Battery) - IP Grade: IP67 (Transceiver / Antenna / Battery)

IP22 (Charger / Adaptor)

- Ex Code: Exib IIB T4 Gb - Battery Capacity: 2200 mAh - Battery Voltage: DC 7.2 V

SIZE DIMENSION 30.2 49 256 @|@|@ NSR 51.4

EQUIPMENT LIST STANDARD - Transceiver & Antenna 1 set - Rechargeable Battery Pack 1 pc - Battery Charger 1 pc - AC/DC Adaptor 1 pc - Belt Clip 1 pc - Wrist Rope 1 pc OPTIONS - External PTT & Skull Mic/Headset 1 set Belt Clip Rechargeable **Battery Pack** AC/DC Adapter **Battery Charger** Wrist Rope Skull Mic/Headset External PTT

