- Strong nylon material used for transmitter case
- True wind speed/direction available
- Up to 4 display units and 6 data output
- Type approval with CCS



**AM-100T TRANSMITTER** 



AM-100R REMOTE BUTTON



**AM-100D DISPLAY UNIT** 

- AM-100 Digital Anemometer is designed for marine use. With case made of nylon and PC material, AM-100 can stand strong wind
  of 60+m/s and can be installed outdoor without corrosion.
- AM-100 can support up to 4 display units to indicate wind speed and direction at four locations onboard. Maximum 6 ports of RS422 output are available, to provide wind data to other navigation devices.
- Real wind direction and speed can be indicated when AM-100 is connected with speed log and compass. The heading and speed
  data can also be provided with COG & SOG from GPS receiver, if the connection with speed log and compass is not possible in
  some cases.







## **SPECIFICATIONS**

Wind direction 0~360° Wind Range:

Wind velocity 0~60 m/s

Wind direction  $\pm 5^{\circ}$ Accuracy:

Wind velocity  $\pm (0.5 + V \times 5\%)$  m/s

AC 110 V/220 V Power Supply:

Output Data: NMEA 0183 (6 ports, RS422), 4800 bps Input Signal: Gyro Compass, NMEA 0183, RS422

Speed Log, NEMA 0183, RS422

Display Capacity: Max 4 Display Units to be connected

Environment: Outdoor -30°C~+70°C, Indoor -15°C~+55°C Size (Transmitter Unit): 627 (H)×605 (L)×243 (propeller diameter) mm

Weight: 4.0 kg (Transmitter unit)

IP Grade: IP22 (Display Unit, Junction Box, Remote Button)

IP66 (Transmitter Unit)

## **EQUIPMENT LIST**

## STANDARD

- Transmitter Unit AM-100T 1 pc - Display Unit AM-100D 1 pc AM-100J - Junction Box 1 pc 40 m - Outdoor Cable 1 pc - Indoor Cable 10 m

1 pc

1 set

OPTIONS

- Remote Button AM-100R - Additional Display Unit AM-100D

- Additional Cables

- Installation Materials







