EX-PRO HANDHELD PHONE

NSR Fire-fighter's portable radiotelephone:

- Meet IMO MSC.338 (91) regulation
- Designed for onboard fire-fighter's communication
- Ex-proof certificated
- Type approval with CCS



According to IMO MSC.338 (91) & SOLAS Chapter II-2, regulation 10.10.4:

Fire-fighter's communication

A minimum of TWO two-way portable radiotelephone apparatus for each fire party for fire-fighter's communication shall be carried on board. Those two-way portable radiotelephone apparatus shall be of an explosion-proof type or intrinsically safe.







SPECIFICATIONS

• FREQUENCY & CHANNEL

- Frequency Range: 156.300∼156.875 MHz

- Channel Space: 25 kHz

- Usable Channels: 19 channels (default)

• TECHNICAL FEATURE

- Output Power: High 3.0 W / Low 0.5 W

- Communication Methods: Simplex
- Warming Up Time: Within 5 sec
- Squelch Control:
- Dual Watch:
√

- Operating Temperature: -20°C∼+60°C

 - Size:
 256 (H)×56 (W)×46.2 (D) mm

 - Weight:
 280 g (Transceiver + Battery)


 - IP Grade:
 IP66 (Transceiver / Antenna / Battery)


.. 55 (114.1555175177411511

IP22 (Charger / Adaptor)

- Ex Code: Exib IIB T4 Gb
- Battery Capacity: 2200 mAh
- Battery Voltage: DC 7.2 V

SIZE DIMENSION





EQUIPMENT LIST

STANDARD

- Transceiver & Antenna ZXF-N2000 1 set - Rechargeable Battery Pack NBT200CX 1 pc - Battery Charger NBT200CU 1 pc - AC/DC Adaptor NBT200CUA 1 pc - Belt Clip 1 pc - Wrist Rope 1 pc

OPTIONS

- External PTT & Skull Mic/Headset ZXF-HM1000 1 set





Rechargeable Battery Pack

Belt Clip





Battery Charger



Skull Mic/Headset







